

| Cubic Inches | Bore | Stroke | Rod | Comp Height | Pin Diam. | Crown Vol | Wght G | Compression Ratio | Alloy | Clearance Guide | | | Part No. |
|--------------|------|--------|-----|-------------|-----------|-----------|--------|-------------------|-------|-----------------|-----|-----|----------|
| | | | | | | | | | | Meas. | Min | Max | |

BIG BLOCK OLDSMOBILE 455 Stroker DISH

1.0, 1.0, 2.0mm File Fit Performance Ring Set included

| | | | | | | | | 72cc | 80cc | 84cc | | | | | |
|-----|-------|-------|-------|-------|-------|---------|-----|------|------|------|------|-------|--------|--------|-----------|
| 488 | 4.155 | 4.500 | 7.100 | 1.260 | 0.990 | -22.0cc | 491 | 10.7 | 10.0 | 9.7 | 4032 | 0.500 | 0.0025 | 0.0033 | 930274555 |
| 495 | 4.185 | | | | | | 503 | 10.8 | 10.1 | 9.8 | | | | | 930274585 |



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
"Min" and **"Max"** is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.