

Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
									Meas.	Min	Max	

HONDA H22 GOLD SERIES 2.2L- FOR USE IN FACTORY FRM (FIBER REINFORCED MATRIX) CYLINDERS ONLY

1.2, 1.2, 2.8mm Performance Ring Set Included

CR calculated at 0.15mm below deck and 0.66mm head gasket thickness

Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Meas.	Min	Max	Part No.
87.00mm	90.7mm	143mm	31mm	22mm	-7.0cc	293	9.2	4032	0.236	0.0016	0.0024	930081525
87.25mm						296	9.2					930081535
87.00mm					-1.0cc	309	10.0	4032	0.236	0.0016	0.0024	930082325
87.25mm						310	10.1					930082335
87.00mm					9.8cc	335	12.0	4032	0.236	0.0016	0.0024	930083125
87.25mm						338	12.1					930083135



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.