

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

LS 6.0L DISH

LSX COMBO pockets - compatible with LS1/2/6 style cathedral port heads & LS3 / L92 style rectangular port heads

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

								62cc	65cc	71cc					
364	4.000	3.622	6.125	1.304	0.927	-12.0cc	430	10.1	9.8	9.2	2618	0.500	0.0046	0.0054	930225400
365	4.005						432	10.1	9.8	9.2					930225405
366	4.010						434	10.1	9.8	9.2					930225410
370	4.030						442	10.2	9.9	9.3					930225430
403	4.005	4.000	6.125	1.110	0.927	-12.0cc	411	11.0	10.7	10.0	4032	0.500	0.0025	0.0033	930219305
404	4.010						413	11.1	10.7	10.1					930219310
408	4.030						421	11.2	10.8	10.2					930219330
402	4.000			1.110R		-14.0cc	399	10.8	10.4	9.8	2618	0.500	0.0046	0.0054	930229400
403	4.005						400	10.8	10.5	9.9					930229405
404	4.010						402	10.8	10.5	9.9					930229410
408	4.030						410	10.9	10.6	10.0					930229430
402	4.000			1.110R		-25cc	400	9.6	9.4	8.9	2618	0.500	0.0046	0.0054	930225500
403	4.005						402	9.7	9.4	8.9					930225505
404	4.010						404	9.7	9.4	8.9					930225510
408	4.030						412	9.8	9.5	9.0					930225530
415	4.000	4.125	6.125	1.050R	0.927	-20.0cc	388	10.4	10.1	9.6	2618	0.500	0.0046	0.0054	930230000
416	4.005						390	10.4	10.1	9.6					930230005
417	4.010						392	10.5	10.2	9.6					930230010
421	4.030						400	10.5	10.2	9.7					930230030

Compression Heights with "R" INCLUDE Oil Support Rails



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.