

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

LS 6.2L DISH (LSA / LS9) - compatible with all LS Heads

Designed for High Boost Applications w/ reduced CH and no valve pockets

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

CR calculated at 0.005" below deck and 0.051 x 4.100" head gasket

							64cc	69cc	72cc						
376	4.065	3.622	6.125	1.299	0.927	-4.5cc	478	10.6	10.0	9.7	2618	0.500	0.0046	0.0054	197813865*
377	4.070						480	10.6	10.0	9.7					197813870*
378	4.075						483	10.6	10.0	9.7					197813875*
379	4.080						485	10.6	10.1	9.8					197813880*

*2618 Alloy, HD 0.188"W H13 Wrist Pin & Hard Anodized Top Ring Groove For Extreme Duty Applications



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.