

Cubic Bore Inches	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
									Meas.	Min	Max	

LS 6.2L DISH

LSX COMBO pockets - compatible with LS1/2/6, LS7, and LS3 / L92 style heads

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

								64cc	70cc	72cc					
376	4.065	3.622	6.125	1.304	0.927	-12.0cc	456	10.1	9.5	9.3	2618	0.500	0.0046	0.0054	930225465
377	4.070							10.1	9.5	9.3					930225470
378	4.075							10.2	9.5	9.4					930225475
379	4.080							10.2	9.6	9.4					930225480
415	4.065	4.000	6.125	1.110R	0.927	-14.0cc	423	10.8	10.2	10.0	2618	0.500	0.0046	0.0054	930229465
416	4.070							10.9	10.2	10.0					930229470
417	4.075							10.9	10.2	10.0					930229475
418	4.080							10.9	10.3	10.1					930229480
415	4.065					-25cc	425	9.7	9.2	9.1	2618	0.500	0.0046	0.0054	930225565
416	4.070							9.7	9.2	9.1					930225570
417	4.075							9.8	9.3	9.1					930225575
418	4.080							9.8	9.3	9.1					930225580
428	4.065	4.125	6.125	1.050R	0.927	-8.0cc	432	11.9	11.1	10.9	4032	0.500	0.0025	0.0033	930225265
429	4.070							11.9	11.2	10.9					930225270
430	4.075							11.9	11.2	11.0					930225275
428	4.065														
429	4.070	10.5	9.9	9.7	930230070										
430	4.075	10.5	9.9	9.8	930230075										
431	4.080	10.5	10.0	9.8	930230080										

Compression Heights with "R" INCLUDE Oil Support Rails

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
"Min" and **"Max"** is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.

