

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

LS 6.2L FLAT TOP

LSX COMBO pockets - compatible with LS1/2/6, LS7, and LS3 / L92 style heads

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

							64cc	70cc	72cc						
376	4.065	3.622	6.098	1.330	0.945	-5.8cc	453	10.8	10.1	9.9	4032	0.500	0.0025	0.0033	930227765
377	4.070						455	10.9	10.2	9.9					930227770
378	4.075						457	10.9	10.2	10.0					930227775
379	4.080						459	10.9	10.2	10.0					930227780
376	4.065	3.622	6.125	1.304	0.927	-5.8cc	467	10.8	10.1	9.9	2618	0.500	0.0046	0.0054	930227065*
377	4.070						469	10.9	10.2	9.9					930227070*
378	4.075						471	10.9	10.2	10.0					930227075*
379	4.080						473	10.9	10.2	10.0					930227080*
376	4.065	3.622	6.125	1.304	0.927	-5.8cc	452	10.8	10.1	9.9	4032	0.500	0.0025	0.0033	930227865
377	4.070						454	10.9	10.2	9.9					930227870
378	4.075						456	10.9	10.2	10.0					930227875
379	4.080						458	10.9	10.2	10.0					930227880
376	4.065	3.622	6.125	1.304	0.927	-5.8cc	466	10.8	10.1	9.9	2618	0.500	0.0046	0.0054	930226865*
377	4.070						468	10.9	10.2	9.9					930226870*
378	4.075						470	10.9	10.2	10.0					930226875*
379	4.080						472	10.9	10.2	10.0					930226880*
415	4.065	4.000	6.125	1.110	0.927	-5.8cc	426	11.9	11.1	10.9	4032	0.500	0.0025	0.0033	930227965
416	4.070						428	11.9	11.1	10.9					930227970
417	4.075						430	11.9	11.1	10.9					930227975
418	4.080						432	11.9	11.2	10.9					930227980
415	4.065	4.000	6.125	1.110R	0.927	-5.8cc	437	11.9	11.1	10.9	2618	0.500	0.0046	0.0054	930227565*
416	4.070						439	11.9	11.1	10.9					930227570*
417	4.075						441	11.9	11.1	10.9					930227575*
418	4.080						443	11.9	11.2	10.9					930227580*
428	4.065	4.125	6.125	1.050R	0.927	-5.8cc	427	12.2	11.4	11.2	2618	0.500	0.0046	0.0054	930227265
429	4.070						429	12.2	11.4	11.2					930227270
430	4.075						431	12.3	11.5	11.2					930227275
431	4.080						433	12.3	11.5	11.2					930227280

Compression Heights with "R" INCLUDE Oil Support Rails

*Available In Multiple Alloys



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.