LS COMBO DOME - compatible with LS1/2/6 style cathedral port heads & LS3 / L92 style rectangular port heads

(Does not fit LS7 or 5.3L 706 & 862 Truck Heads)

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio 64cc	68cc	70cc	Alloy	Clearance Guide Meas.	Min	Max	Part No.
402	4.000	4.000	6.125	1.110R	0.927	9.2cc	454	14.1	13.3	12.9	2618	0.500	0.0046	0.0054	930229600
403	4.005						456	14.1	13.3	13.0					930229605
404	4.010						457	14.1	13.3	13.0					930229610
408	4.030						465	14.2	13.4	13.1					930229630
415	4.065						479	14.4	13.6	13.3					930229665
416	4.070						480	14.5	13.7	13.3					930229670
417	4.075						482	14.5	13.7	13.3					930229675
418	4.080						484	14.5	13.7	13.4					930229680

Compression Heights with “R” INCLUDE Oil Support Rails

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
“Min” and “Max” is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040” gasket unless otherwise noted.