

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio		Alloy	Clearance Guide			Part No.
											Meas.	Min	Max	

LT 6.2L FLAT TOP & DOME - compatible with GM LT1 / L86 / LT4 heads

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

									60cc	65.5cc				
376	4.065	3.622	6.125	1.304	0.927	-4.5cc	481	11.6	10.8	2618	0.500	0.0046	0.0054	930228765*
377	4.070						483	11.6	10.8					930228770*
379	4.080						485	11.6	10.9					930228780*
415	4.065	4.000	6.125	1.105	0.927	-4.3cc	439	12.7	11.9	2618	0.500	0.0046	0.0054	930165365*
416	4.070						441	12.7	11.9					930165370*
428	4.125					-6.1cc	455	12.7	11.9	2618	0.500	0.0046	0.0054	930173225*
429	4.130						457	12.7	11.9					930173230*

*Hard Anodized Top Ring Groove For Extreme Duty Applications, designed for aftermarket rods



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.