

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

NHRA LEGAL FORD 5.0L MODULAR 4-VALVE (2014, 2015 COBRA JET)

Available in bore sizes up to the legal NHRA limit of +0.080" oversize; call for sizes/other tech; NHRA PN 197736200

Requires 1.2, 1.2, 2.5mm Ring Set (Not Included)

								57cc						
302	3.630	3.650	5.933	1.167	0.866	-8.8cc	350	9.5	2618	0.500	0.0025	0.0033	197736230*	
306	3.650						356	9.6					197736250*	
314	3.700						372	9.8					197736200*	
314	3.702						373	9.8					197736202*	
315	3.705						374	9.8					197736205*	
315	3.707						374	9.9					197736207*	
316	3.710						375	9.9					197736210*	

*2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications.



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.