

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

NHRA LEGAL FORD 5.0L MODULAR 4-VALVE (2016 COBRA JET)

Available in bore sizes up to the legal NHRA limit of +0.080" oversize; call for sizes/other tech; NHRA PN 930049900

Requires 1.2, 1.2, 2.5mm Ring Set (Not Included)

										57cc			
302	3.630	3.650	5.933	1.167	0.866	7.3cc	377	12.0	2618	0.500	0.0016	0.0023	930049930*
306	3.650						384	12.1					930049950*
314	3.700						400	12.3					930049900*
314	3.702						401	12.3					930049902*
315	3.705						402	12.4					930049905*
315	3.707						402	12.4					930049907*
316	3.710						403	12.4					930049910*

*Hard Anodized Top Ring Groove For Extreme Duty Applications.

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.