

| Bore | Stroke | Rod | Comp Height | Pin Diam. | Crown Vol | Wght G | Compression Ratio | Alloy | Clearance Guide | | | Part No. |
|------|--------|-----|-------------|-----------|-----------|--------|-------------------|-------|-----------------|-----|-----|----------|
| | | | | | | | | | Meas. | Min | Max | |

NISSAN RB26DETT (SKYLINE) 2.6L

NOTE : Must check oil squirter clearance, possible modification needed.

1.2, 1.2, 2.8mm Performance Ring Set Included

CR calculated at 0.1mm above deck and 1.57mm head gasket thickness

65cc

| | | | | | | | | | | | | |
|---------|--------|---------|---------|------|--------|-----|-----|------|-------|--------|--------|------------|
| 86.50mm | 73.7mm | 121.5mm | 30.25mm | 21mm | 16.0cc | 366 | 8.5 | 2618 | 0.236 | 0.0031 | 0.0039 | 930110205* |
| 87.00mm | | | | | | 372 | 8.6 | | | | | 930110225* |

*Hard Anodized Top Ring Groove For Extreme Duty Applications



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.