

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.
												Meas.	Min	Max	

**SMALL BLOCK CHEVY 22°/23° FLAT TOP Gasported**

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

								58cc	64cc	70cc					
374	4.125	3.500	6.000	1.250	0.927	-7.8cc	453	11.3	10.5	9.9	2618	0.500	0.0061	0.0069	197756525
375	4.130						455	11.3	10.5	9.9					197756530
376	4.135						457	11.3	10.6	9.9					197756535
377	4.140						459	11.3	10.6	9.9					197756540
378	4.145						461	11.4	10.6	9.9					197756545
379	4.150						463	11.4	10.6	9.9					197756550
380	4.155						464	11.4	10.6	10.0					197756555
381	4.160						466	11.4	10.7	10.0					197756560
381	4.165						468	11.5	10.7	10.0					197756565



**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.  
 "Min" and "Max" is the suggested range of clearance over the coating for each application.  
**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted.