

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

SMALL BLOCK CHEVY 2bbl LIGHT WEIGHT FLAT TOP Asymmetrical Valve Pockets

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

Light Weight 92g pins Included

								58cc	64cc	70cc					
357	4.030	3.500	5.700	1.550	0.927	-2.4cc	411	11.6	10.8	10.1	4032	0.500	0.0036	0.0044	930206530
359	4.040						415	11.7	10.8	10.1					930206540
362	4.060						423	11.8	10.9	10.2					930206560
357	4.030	3.500	6.000	1.250	0.927	-2.4cc	376	11.6	10.8	10.1	4032	0.250	0.0036	0.0044	930206630
359	4.040						379	11.7	10.8	10.1					930206640
362	4.060						386	11.8	10.9	10.2					930206660
357	4.030	3.500	6.125	1.125	0.927	-2.4cc	360	11.6	10.8	10.1	4032	0.250	0.0036	0.0044	930206730
359	4.040						364	11.7	10.8	10.1					930206740
362	4.060						370	11.8	10.9	10.2					930206760
383	4.030	3.750	6.000	1.125	0.927	-2.4cc	360	12.4	11.5	10.7	4032	0.250	0.0036	0.0044	930206730
385	4.040						364	12.4	11.5	10.7					930206740
388	4.060						370	12.5	11.6	10.8					930206760

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.

