

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.
										Meas.	Min	Max	

SMALL BLOCK MOPAR (LA) / 340, 360 DISH

1.0, 1.0, 2.0mm File Fit Performance Ring Set included

Does not fit stock rod end width. Aftermarket rod must be used.

								60cc	65cc	70cc					
408	4.030	4.000	6.123	1.460	0.984	-28cc	487	9.7	9.2	8.9	2618	0.500	0.0046	0.0054	930271130
410	4.040						492	9.7	9.3	8.9					930271140
416	4.070						505	9.8	9.4	9.0					930271170
408	4.030	4.000	6.123	1.460	0.984	-16cc	480	10.9	10.4	9.9	4032	0.500	0.0025	0.0033	930271030
410	4.040					484	11.0	10.4	9.9	930271040					
416	4.070					496	11.1	10.5	10.0	930271070					



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.